



**The Clorox Company**  
 1221 Broadway  
 Oakland, CA 94612  
 Tel. (510) 271-7000

**Material Safety  
 Data Sheet**

<b>I Product:</b> GREEN WORKS™ NATURAL ALL PURPOSE CLEANER		<b>Description:</b> LIQUID WITH LEMON ODOR																						
<b>Other Designations</b>		<b>Distributor</b>																						
For Medical Emergencies call: 1-800-446-1014 For Transportation Emergencies, call Chemrec: 1-800-424-9300		Clorox Sales Company 1221 Broadway Oakland, CA 94612																						
<b>II Health Hazard Data</b>																								
Eye irritant. May cause skin irritation. No medical conditions are known to be aggravated by exposure to this product. <b>FIRST AID:</b> <b>EYE CONTACT:</b> Immediately rinse with plenty of water. If irritation persists, call a doctor. <b>INGESTION:</b> Drink a glassful of water. Call a doctor or poison control center. <b>SKIN CONTACT:</b> Rinse with plenty of water. If irritation persists, call a doctor. <b>INHALATION:</b> Move person to fresh air. If breathing problems develop, call a doctor.																								
<b>III Hazardous Ingredients</b>																								
<table border="0"> <tr> <td>Ingredient</td> <td>Concentration</td> <td>Worker Exposure Limit</td> </tr> <tr> <td>Alkyl polyglycoside</td> <td>CAS # 68515-73-1</td> <td>2 - 5% not established</td> </tr> <tr> <td>Ethyl alcohol</td> <td>CAS # 64-17-5</td> <td>1 - 3% 1000 ppm - TLV-TWA</td> </tr> <tr> <td></td> <td></td> <td>1000 ppm - OSHA PEL</td> </tr> <tr> <td>TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average</td> <td></td> <td></td> </tr> <tr> <td>OSHA-PEL = OSHA Permissible Exposure Limit - Time Weighted Average</td> <td></td> <td></td> </tr> <tr> <td colspan="3">None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.</td> </tr> </table>				Ingredient	Concentration	Worker Exposure Limit	Alkyl polyglycoside	CAS # 68515-73-1	2 - 5% not established	Ethyl alcohol	CAS # 64-17-5	1 - 3% 1000 ppm - TLV-TWA			1000 ppm - OSHA PEL	TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average			OSHA-PEL = OSHA Permissible Exposure Limit - Time Weighted Average			None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.		
Ingredient	Concentration	Worker Exposure Limit																						
Alkyl polyglycoside	CAS # 68515-73-1	2 - 5% not established																						
Ethyl alcohol	CAS # 64-17-5	1 - 3% 1000 ppm - TLV-TWA																						
		1000 ppm - OSHA PEL																						
TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average																								
OSHA-PEL = OSHA Permissible Exposure Limit - Time Weighted Average																								
None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists.																								
<b>IV Special Protection and Precautions</b>		<b>V Transportation and Regulatory Data</b>																						
<b>Hygienic Practices:</b> Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods. <b>Engineering Controls:</b> Use local exhaust to minimize exposure to product mist. <b>Personal Protective Equipment:</b> Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.		<b>DOT/ATA/IMDG:</b> Not restricted. <b>EPA - SARA Title III/CERCLA:</b> This product is regulated under Sections 311/312. This product contains no chemicals which are regulated under Section 313 or regulated under Section 304/CERCLA.																						
<b>VI Spill Procedures/Waste Disposal</b>																								
<b>Spill Procedures:</b> Absorb and containize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. <b>Waste Disposal:</b> Dispose of in accordance with all applicable federal, state, and local regulations.																								
<b>VIII Fire and Explosion Data</b>		<b>IX Physical Data</b>																						
<b>Flash Point:</b> >200°F (closed cup) <b>Fire Extinguishing Agents:</b> Dry chemical, carbon dioxide (CO <sub>2</sub> ), foam, or water spray.		pH ..... ~7.0 Specific gravity ..... 1.0 Solubility in water ..... Soluble																						

© 1983, 1991 THE CLOROX COMPANY  
 DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH

DATE PREPARED 10/07